



2-Cylinder Inground Lift RAV1110LR

GTIN: 4057612815399

SKU: RAV1110LR

3.5 t, with very flat swivel arms and height-adjustable turntable plug-in system, lower swivel height 80 mm

DESCRIPTION

- Perfect synchronization between cylinders regardless of load distribution.
- Equipped with safety valve to prevent overloading and in case of hydraulic pipe fracture.
- Self-controlled lowering speed.
- All mechanical, hydraulic and electrical components manufactured in compliance with the respective European Safety Standard.

- Maintenance free cylinders: Each column features a maintenance-free lifting cylinder
- Double joint: Cross bar with double joint to eliminate vibrations
- Safe - Mechanical lock: Mechanical safety latch with automatic engagement, ensuring maximum safety when lift is in standing position.
- Hard chrome columns: Hard chrome columns grant long life
- Maintenance free guides: Columns guides in oil bath, maintenance free

- Version with 2160 mm clearance between the columns
- Extra low profile arms, parallel to the floor
- Double thread pads with a min. height of 80 mm only

TECHNICAL DETAILS

Number of rams	2
Inground lift design	Swivel arm
Type of installation	Surface mounted
Capacity	3500kg
Max. lifting height	2019mm
Plunger diameter	180mm
Column distance	2160mm
Wheel alignment	Not possible
Arm layout	Symmetrical
Telescopic front arms	2-fold
Telescopic rear arms	2-fold
Min. lifting arm length	500mm
Max. lifting arm length	1070mm
Bottom clearance	80mm
Width	2720mm
Installation depth	2496mm