



2-Cylinder Inground Lift RAV1110NK

GTIN: 4057612815412

SKU: RAV1110NK



3.5 t, with swivel arms and height-adjustable
turntable plug-in system, lower swing height 95 mm

DESCRIPTION

- Perfect synchronization between cylinders regardless of load distribution.
- Equipped with safety valve to prevent overloading and in case of hydraulic pipe fracture.
- Self-controlled lowering speed.
- All mechanical, hydraulic and electrical components manufactured in compliance with the respective European Safety Standard.

- Maintenance free cylinders: Each column features a maintenance-free lifting cylinder
- Double joint: Cross bar with double joint to eliminate vibrations
- Safe - Mechanical lock: Mechanical safety latch with automatic engagement, ensuring maximum safety when lift is in standing position.
- Hard chrome columns: Hard chrome columns grant long life
- Maintenance free guides: Columns guides in oil bath, maintenance free

- Waterproof inground frame: steel frame and plastic cover
- Pads can be adjusted in height and are suitable for quick housing of extensions
- Min. pad height 95 mm
- Vehicle access completely free
- Extra low profile arms, parallel to the floor

ACCESSORIES**Product 199528**
199528**Product 199534**
199534**Product 200182**
200182**Spacers 80 mm**

S224A3

For Fiat Ducato, Peugeot Boxer and Citroën Jumper | for quick drop-in of the K arms, bushing Ø 45 mm | 1 set / 4 pieces

**Spacers 140 mm**

S224A4

For Fiat Ducato, Peugeot Boxer and Citroën Jumper | for quick drop-in of the K arms, bushing Ø 45 mm | 1 set / 4 pieces

**Spacers 200 mm, Ø 45 mm**

S370A18

For Fiat Ducato, Peugeot Boxer and Citroën Jumper | bushing Ø 45 mm | 1 set / 4 pieces

TECHNICAL DETAILS

Number of rams	2
Inground lift design	Swivel arm
Type of installation	Surface mounted
Capacity	3500kg
Max. lifting height	2063mm
Plunger diameter	120mm
Column distance	1340mm
Wheel alignment	Not possible
Arm layout	Asymmetrical
Telescopic front arms	3-fold
Telescopic rear arms	3-fold
Min. lifting arm length	500mm
Max. lifting arm length	1070mm
Bottom clearance	95mm
Width	3066mm