



2-Cylinder Inground Lift RAV1125

GTIN: 4057612815436

SKU: RAV1125

3.5 t, with flat beam support, extendable in the direction of travel

DESCRIPTION

- Perfect synchronization between cylinders regardless of load distribution.
- Equipped with safety valve to prevent overloading and in case of hydraulic pipe fracture.
- Self-controlled lowering speed.
- All mechanical, hydraulic and electrical components manufactured in compliance with the respective European Safety Standard.

- Maintenance free cylinders: Each column features a maintenance-free lifting cylinder
- Double joint: Cross bar with double joint to eliminate vibrations
- Safe - Mechanical lock: Mechanical safety latch with automatic engagement, ensuring maximum safety when lift is in standing position.
- Hard chrome columns: Hard chrome columns grant long life
- Maintenance free guides: Columns guides in oil bath, maintenance free

- Waterproof inground frame: steel frame and plastic cover
- Lift with extra-low platforms: only 60 mm
- Platforms can be adjusted in length

TECHNICAL DETAILS

Number of rams	2
Inground lift design	Flat beam
Type of installation	Surface mounted
Capacity	3500kg
Max. lifting height	1990mm
Plunger diameter	120mm
Column distance	1340mm
Wheel alignment	Not possible
Length	1990mm
Width	1620mm
Foundation - length	1670mm
Foundation - width	295mm