4-post lift RAV4401 230-400 V - 3 Ph - 60 Hz

GTIN: 5063084194572

SKU: RAV.4401X.194572

4.0 t, electrohydraulic, symmetrical, with level runways, track length 4460 mm, wheel alignment optional, above ground | 3 x 230/400 V / 60 Hz

DESCRIPTION

- The hydraulic cylinder is located inside the fixed platform and is thus perfectly protected
- High-resistant, galvanised and pre-stretched metal cables
- Large-diameter pulleys with self-lubricating and maintenance-free bushes
- Automatic mechanical back-up safety devices (every 100 mm) with pneumatic release allowing stationary operation with unladen cables
- Immediate-triggering safety stud devices in case a cable slackens or fails
- Automatic anti-toe trap alarm during final stages of lift descent
- Mechanical, electrical and hydraulic safety devices in compliance with the prevailing standard for CE marking
- Low-voltage (24 V) electrical system with control circuit

- Version with flat platforms

ACCESSORIES

Jacking beam J17X
VSG.J17XX.901989
2.0 t, Hydraulic, with hand-pump | for all hydraulic 4-post lifts / scissor lifts

Jacking beam J20NX
VSG.J20NX.901941
2.0 t, hydraulic, operated by means of hand-pump

Jacking beam J20PNX
VSG.J20PN.901767
2.0 t, air-hydraulic

Jacking beam J20PNXL
VSG.J20PN.901682
2.0 t, air-hydraulic

Jacking beam J20PNR
VSG.J20PN.901583
2.0 t, air-hydraulic

Jacking beam J20PNRL
VSG.J20PN.901422
2.0 t, air-hydraulic

Jacking beam J30PKL
VSG.J30PK.902368
3.0 t, air-hydraulic

Jacking beam J30X
VSG.J30XX.901514
3.0 t, hydraulic, operated by means of hand-pump

Jacking beam J30PX
VSG.J30PX.901781
3.0 t, air-hydraulic

Jacking beam J30PXL
VSG.J30PX.901804
3.0 t, air-hydraulic

Jacking beam J30PR
VSG.J30PR.901392
3.0 t, air-hydraulic

Jacking beam J30PRL
VSG.J30PR.901828
3.0 t, air-hydraulic

Jacking beam J40PRL
VSG.J40PR.901965
4.0 t, air-hydraulic

Jacking beam J40PXL
VSG.J40PX.902191
4.0 t, air-hydraulic

Jacking beam J40PKL
VSG.J40PK.901880
4.0 t, air-hydraulic

Jacking beam J40PY
VSG.J40PY.902214
4.0 t, air-hydraulic

Jacking beam J50PHT
VSG.J50PH.902238
5 t, 392 mm stroke, air-hydraulic, telescopic jack, roller bearings in the track, air supply on site

Jacking beam J50PHA
VSG.J50PH.902177
5.0 t, air-hydraulic

ACCESSORIES

Drive-on ramp kit
S4351A2
Long, 1100 mm | for 4-post lifts RAV4401, RAV4402, RAV4401SI | 1 pair

Drive-through ramp kit
S4351A1
For RAV4401, RAV4402, RAV4401SI | 1 set / 2 pieces

Post covers for 4-post lift
S401A8



Seat for turntables | plates and slip plates excluded | 1 set
STDA140
For RAV4350, RAV4401, RAV4405L, RAV4501L, RAV4651L, RAV4800

Rubber pads
S505A7
20 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N2.193858, RAV.650N2.193520, RAV.650N2.193667, RAV.650N6.193964, RAV.650N5.193902, RAV.660N2.193360, RAV.650N5.193018, RAV.650N6.193025, RAV.640N5.193049, RAV.640N4.192998, RAV.640N3.192981, RAV.650N2.193384 and RAV.650N5.193919 | 1 set / 4 pieces

Rubber pads
S505A6
40 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N2.193858, RAV.650N2.193520, RAV.650N2.193667, RAV.650N6.193964, RAV.650N5.193902, RAV.660N2.193360, RAV.650N5.193018, RAV.650N6.193025, RAV.640N5.193049, RAV.640N4.192998, RAV.640N3.192981, RAV.650N2.193384 and RAV.650N5.193919 | 1 set / 4 pieces

Rubber pads
S505A9
60 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N6.193964, RAV.660N2.193360, RAV.650N6.193025, RAV.640N5.193049 and RAV.640N4.192998 | 1 set / 4 pieces

Rubber pads
S505A5
120 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N2.193858, RAV.650N2.193520, RAV.650N2.193667, RAV.650N6.193964, RAV.650N5.193902, RAV.660N2.193360, RAV.650N5.193018, RAV.650N6.193025, RAV.640N5.193049, RAV.640N4.192998, RAV.640N3.192981, RAV.650N2.193384 and RAV.650N5.193919 | 1 set / 4 pieces

Rubber pads
S505A1
200 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N2.193858, RAV.650N2.193520, RAV.650N2.193667, RAV.650N6.193964, RAV.650N5.193902, RAV.660N2.193360, RAV.650N5.193018, RAV.650N6.193025, RAV.640N5.193049, RAV.640N4.192998, RAV.640N3.192981, RAV.650N2.193384 and RAV.650N5.193919 | 1 set / 4 pieces

Traverses for XS30-CAT
S505A2
For vans and off-road vehicles | 1 set / 2 pieces

TECHNICAL DETAILS

Number of columns	4
Mode of drive	Electrohydraulic
Control	Electric
Type of installation	Floor mounted
Capacity	4000kg
Max. lifting height	1905mm
Drive-on-height	150mm
Clear span between	2800mm
Clear span between (out)	3155mm
Column height	2614mm
Drive-through width	2470mm
Wheel alignment	Optional
Length of platforms	4460mm
Width of platforms	500mm
Space of platforms	910 - 1250mm
Set-up length with drive-on ramps	5418mm
Driving power	2,6kW
Electrical connection	230/400 V, 60 Hz
Country of Origin, customs	IT