



2-post lift KPX40AVE

GTIN: 5063084198235

SKU: RAV.KPX40.198235

4.0 t, electromechanical, push-button control on both sides, symmetrical posts, asymmetrical AV arms, 3-stage long arms, 3-stage short arms, TEq-Link, energy kit | Grey (RAL 7040)

DESCRIPTION

Legend Series - From History to the Future

- Up-to-date design: modern outline that brings modernity and usability to the workshop
- Innovative DNA: long-standing high-quality components and tested for 20000 cycles
- Future-proof: lifts designed for the TEq-Link workshop connectivity system

Emerging from the bestselling 2-post lifts, the Legend Series consolidates the engineering knowledge of Ravaglioli and shapes it into an innovative package. Looking towards the future while always honouring the past, Ravaglioli has set an important goal for itself - let the performance meet the design.

- The geometry of the arms is designed to lift every type of car from classic city cars to vans.
- The innovative AV ("All Vehicles") arms extend 20% further than conventional arms, allowing them to reach the lifting points of a wide range of vehicles.
- E version equipped with double control panel and Energy kit.

- High-performance motors.
- Automatic arm lock and automatic ground release: conical geometry with self-locking effect.
- Permanent and automatic lubrication of the nuts to ensure effective operation during upward and downward movement.
- High-strength rolled steel screw for maximum durability.
- Arms made of special steel, with first stage height just 70 mm and second stage height 85 mm.
- Equipped with an acoustic anti toe trap system - Free from mechanical foot guards.
- Premium quality of components:
 - Aluminium pulley with cooling function.
 - Long lasting bearings.
 - 50% longer, bronze load nut.
 - Motors with reinforced and cooling casing.
 - Solid automatic arm locking.

ACCESSORIES**Eyebolt**

VSG.2CELM.901927

3.5 t - 4.2 t | facilitates installation of the lift, can be used again for other installations | 1 set

**Inground cable connection kit**

VSG.2CELM.902498

Allows columns connection cables to be placed inground | 1 piece

**Support plates**

VSG.2CALL.901453

4 / 4.2 / 4.5 t | allows installation on floors with poor capacity or lower concrete thickness | 1 set / 2 pieces

**Vehicles lift platforms**

VSG.2CALL.902818

Ramp height 60 mm, for extremely low vehicles | 1 set / 2 pieces

**Stands for alignment**

VSG.2CALL.902085

1 set / 4 pieces

**Tool trays**

VSG.2CALL.902641

Magnetic | 1 set / 2 pieces

TECHNICAL DETAILS

Number of columns	2
Capacity	4000kg
Column layout	Symmetrical
Mode of drive	Electromechanical
Control	Electric
Type of installation	Floor mounted
TeqLink	Standard
Max. lifting height	1982mm
Lifting time	58s
Min. plate height	97mm
Max. plate height	127mm
Clear span between	2700 - 2800mm
Clear span between (out)	3194 - 3094mm
Column height	2863mm
Drive-through width	2504mm
Required ceiling height	4100mm
Surface coating	Powder coated
Arm layout	Asymmetrical
Telescopic front arms	3-fold
Telescopic rear arms	3-fold
Min. front arm length	470mm
Max. front arm length	1039mm
Min. rear arm length	725mm
Max. rear arm length	1480mm

Driving power	2 x 3,5kW
Electrical connection	400 V, 50 Hz
Phases	3
Width	3428 - 3528mm
Height	4000mm
Max. height	4000mm