



## **Commercial vehicle scissor lift RAV709NI**

GTIN: 4057612818079

SKU: RAV709NI


9 t, elektro-hydraulic, platform length 6000 mm,  
inground

### **DESCRIPTION**

Heavy-duty scissor lift for easy lifting of vans, motorhomes, and small trucks. The lift is available with either 9 or 13 t lifting capacity. Track length 6 or 7 m.

- Space-saving
- Perfect synchronisation with automatic compensation
- Durable construction with power reserves
- Hydraulic control of the synchronisation of both platforms, independent of the load distribution. Automatic hydraulic levelling system in the zero position.
- Powerful hydraulic unit for fast lifting and lowering times.
- Platform surfaces made of non-slip bulb plate.
- Foot protection guaranteed by standard CE-stop.
- Special primer and durable top coat provide perfect corrosion protection of the platforms. Floor bearings and scissor elements are cathoresis and powder coated.
- Rollover and roll-back protection at the ends of the guide rails protect the vehicle against rolling down.
- The lift's jointed pins are equipped with self-lubricating bearings.
- The control panel has a hydraulic power unit that is pre-assembled at the factory. It is connected to the lifting platform, thus significantly reducing the installation costs. The hydraulic power unit can be installed on the left or right-hand side.
- Documents or laptops find their place on the integrated storage area. Also perfectly suited as a writing support.
- Durable push buttons permit secure operation of the lift.
- It is possible to couple two lifts together in order to operate them synchronously. Thus, runways can be operated at the same height or individually, obtaining two independent workplaces.
- Pneumatically operated, mechanical safety device with cluster gears guarantee maximum safety for vehicle and

user when raised

**ACCESSORIES****Product 198594**

198594

**Drive-on ramp kit above ground |  
2950 mm | lacquered**


S720A5

2950 mm, lacquered version, dowel to the floor (fixing material not included) | incl. cover plates for hydraulic hoses | 1 set / 2 pieces

**Jacking beam J50PHT**

VSG.J50PH.902238

5 t, 392 mm stroke, air-hydraulic, telescopic jack, roller bearings in the track, air supply on site

**Drive-on ramp kit above ground |  
3700 mm | lacquered**

S720A6

3700 mm, lacquered version, dowel to the floor (fixing material not included) | incl. cover plates for hydraulic hoses | 1 set / 2 pieces

**TECHNICAL DETAILS**

<b>Scissor lift design</b>	Scissors with runways
<b>Mode of drive</b>	Electrohydraulic
<b>Type of installation</b>	Surface mounted
<b>Capacity</b>	9000kg
<b>Max. lifting height at floor level</b>	1680mm
<b>Lifting time</b>	65s
<b>Lifting time loaded</b>	65s
<b>Lowering time</b>	60s
<b>Lowering time loaded</b>	60s
<b>Play detector</b>	Not possible
<b>Drive-on-height</b>	360mm
<b>Surface coating</b>	Cathodic electrodeposition coating (CEC)
<b>Wheel alignment</b>	Not possible
<b>Length of platforms</b>	6000mm
<b>Width of platforms</b>	750mm
<b>Wheel free lift</b>	Not possible
<b>Driving power</b>	3,5kW
<b>Electrical connection</b>	400 V, 50 Hz
<b>Length</b>	6600mm
<b>Width</b>	2650mm
<b>Country of Origin, customs</b>	IT