



## **Commercial vehicle scissor lift RAV825.13I**

SKU: RAV825.13I

25 t, electrohydraulic, platform length 13000 mm,  
with safety latch, inground

---

### **DESCRIPTION**

Commercial vehicle lifts

- No cross rails or torsion bars between lifting platforms. Maximum accessibility in the working area.
- Electronic synchronisation of the platforms, independently of the load distribution.
- Mechanical locking device with automatic engagement and pneumatic release, ensuring maximum safety when lift is in standing position.
- All pivot points made with self lubricating bushings for long life.
- Platform surface in ribbed anti-slip steel plate.
- The best solution for a rational workshop:
  - space-saving when lift is raised
  - obstacle free floor space when lift is fully lowered.

**TECHNICAL DETAILS**

<b>Scissor lift design</b>	Scissors with runways
<b>Mode of drive</b>	Electrohydraulic
<b>Type of installation</b>	Surface mounted
<b>Capacity</b>	25000kg
<b>Max. lifing height at floor level</b>	1750mm
<b>Play detector</b>	Not possible
<b>Surface coating</b>	Powder coated
<b>Corrosion preventing</b>	Cathodic electrodeposition coating (CEC)
<b>Wheel alignment</b>	Not possible
<b>Length of platforms</b>	13000mm
<b>Width of platforms</b>	750mm
<b>Wheel free lift</b>	Not possible
<b>Driving power</b>	4 x 2,6kW
<b>Electrical connection</b>	400 V, 50 Hz
<b>Length</b>	13000mm
<b>Width</b>	2650mm
<b>Country of Origin, customs</b>	IT