



Double scissor lift RAV509IF 230-400 V - 3 Ph - 60 Hz

GTIN: 5063084196354

SKU: RAV.509IF.196354

3.5 t, electrohydraulic, inground | 3 x 230/400 V / 60 Hz

DESCRIPTION

Fixed length of platforms for easy use. The best solution for a rational workshop.

- Space-saving when lift is all raised
- Completely free floor space when lift is fully lowered

- All pivot points made with self lubricating bushings for long life
- Every time the platforms reach the floor, the lift is perfectly levelled thanks to a patented valve
- Mechanical locking device with automatic engagement and pneumatic release, ensuring maximum safety when lift is in standing position

ACCESSORIES**Traverses for XS30-CAT**

S505A2

For vans and off-road vehicles | 1 set / 2 pieces

**Drive-on ramp kit**

S540A4

Additional ramps on the short ramp side | 1 set

TECHNICAL DETAILS

Scissor lift design	Double scissors
Mode of drive	Electrohydraulic
Type of installation	Surface mounted
Capacity	3500kg
Max. lifing height at floor level	1825mm
Lifting time	41s
Lowering time	41s
Play detector	Not possible
Drive-on-height	255mm
Wheel alignment	Not possible
Length of platforms	1580mm
Width of platforms	510mm
Wheel free lift	Not possible
Driving power	2,6kW
Electrical connection	230/400 V, 60 Hz
Phases	3
Length	1610mm
Width	1920mm