



## **Double scissor lift RAV510IQ**

GTIN: 5063084196538

SKU: RAV.510IX.196538

3.5 t, electrohydraulic, TEq-Link, inground

---

### **DESCRIPTION**

Extensible platforms to reach pick up points of the more demanding vehicles. The best solution for a rational workshop.

- Space-saving when lift is all raised
- Completely free floor space when lift is fully lowered
  
- All pivot points made with self lubricating bushings for long life
- Every time the platforms reach the floor, the lift is perfectly levelled thanks to a patented valve
- Mechanical locking device with automatic engagement and pneumatic release, ensuring maximum safety when lift is in standing position

**ACCESSORIES****Traverses for XS30-CAT**

S505A2

For vans and off-road vehicles | 1 set / 2 pieces

**Drive-on ramp kit**

S540A4

Additional ramps on the short ramp side | 1 set

**TECHNICAL DETAILS**

|   |                  |
|---|------------------|
| <b>Scissor lift design</b>                | Double scissors  |
| <b>TeqLink</b>                            | Standard         |
| <b>Mode of drive</b>                      | Electrohydraulic |
| <b>Type of installation</b>               | Surface mounted  |
| <b>Capacity</b>                           | 3500kg           |
| <b>Max. lifting height at floor level</b> | 1825mm           |
| <b>Lifting time</b>                       | 41s              |
| <b>Lowering time</b>                      | 41s              |
| <b>Play detector</b>                      | Not possible     |
| <b>Drive-on-height</b>                    | 265mm            |
| <b>Wheel alignment</b>                    | Not possible     |
| <b>Length of platforms</b>                | 1900mm           |
| <b>Width of platforms</b>                 | 510mm            |
| <b>Wheel free lift</b>                    | Not possible     |
| <b>Driving power</b>                      | 2,6kW            |
| <b>Electrical connection</b>              | 230 V, 50 Hz     |
| <b>Length</b>                             | 1940mm           |
| <b>Width</b>                              | 1920mm           |