



## **Double scissor lift RAV540**

GTIN: 5063084195234

SKU: RAV.540XX.195234

4.0 t, low-profile (135 mm), electrohydraulic, above ground

---

### **DESCRIPTION**


High capacity model with longer lifting plates

- Mechanical locking device with automatic engagement and pneumatic release, ensuring maximum safety when lift is in standing position
- All pivot points made with self lubricating bushings for long life
- Hydraulic levelling system by means of a patented synchronisation device assures constantly levelled lifting platforms regardless of weight distribution
- No cross rails or torsion bars between lifting platforms (for maximum accessibility in the working area)
- Controlled speed during initial lifting and final lowering phase
- Audible alarm during the final lowering phase
- Forged scissors ends to grant maximum resistance to load
  
- Drive-on-height 135 mm

**ACCESSORIES****Traverses for XS30-CAT**


S505A2

For vans and off-road vehicles | 1 set / 2 pieces

**Hose cover 1 m | for surface installation**


S518A20

1 m | for surface installation

**Drive-on ramp kit**

S540A1

Long additional ramps for low ground clearance vehicles

**Recessed installation kit**

S540A2

**TECHNICAL DETAILS**

<b>Scissor lift design</b>	Double scissors
<b>Mode of drive</b>	Electrohydraulic
<b>Type of installation</b>	Floor mounted
<b>Capacity</b>	4000kg
<b>Max. lifting height</b>	2000mm
<b>Lifting time loaded</b>	46s
<b>Lowering time loaded</b>	27s
<b>Play detector</b>	Not possible
<b>Drive-on-height</b>	135mm
<b>Wheel alignment</b>	Not possible
<b>Length of platforms</b>	2060mm
<b>Width of platforms</b>	620mm
<b>Space of platforms</b>	790mm
<b>Wheel free lift</b>	Not possible
<b>Driving power</b>	2,6kW
<b>Electrical connection</b>	230/400 V, 50 Hz
<b>Phases</b>	3
<b>Noise level</b>	≤70dB(A)
<b>Length</b>	2080mm
<b>Width</b>	2030mm
<b>Height</b>	2000mm
<b>Weight</b>	850kg