



Double scissor lift RAV540

GTIN: 5063084195234

SKU: RAV.540XX.195234

4.0 t, low-profile (135 mm), electrohydraulic, above ground

DESCRIPTION

High capacity model with longer lifting plates


- Mechanical locking device with automatic engagement and pneumatic release, ensuring maximum safety when lift is in standing position
- All pivot points made with self lubricating bushings for long life
- Hydraulic levelling system by means of a patented synchronisation device assures constantly levelled lifting platforms regardless of weight distribution
- No cross rails or torsion bars between lifting platforms (for maximum accessibility in the working area)
- Controlled speed during initial lifting and final lowering phase
- Audible alarm during the final lowering phase
- Forged scissors ends to grant maximum resistance to load

- Drive-on-height 135 mm

ACCESSORIES**Traverses for XS30-CAT**


S505A2

For vans and off-road vehicles | 1 set / 2 pieces

**Hose cover 1 m | for surface installation**


S518A20

1 m | for surface installation

**Drive-on ramp kit**

S540A1

Long additional ramps for low ground clearance vehicles

**Recessed installation kit**

S540A2

TECHNICAL DETAILS

Scissor lift design	Double scissors
Mode of drive	Electrohydraulic
Type of installation	Floor mounted
Capacity	4000kg
Max. lifting height	2000mm
Lifting time loaded	46s
Lowering time loaded	27s
Play detector	Not possible
Drive-on-height	135mm
Wheel alignment	Not possible
Length of platforms	2060mm
Width of platforms	620mm
Space of platforms	790mm
Wheel free lift	Not possible
Driving power	2,6kW
Electrical connection	230/400 V, 50 Hz
Phases	3
Noise level	≤70dB(A)
Length	2080mm
Width	2030mm
Height	2000mm
Weight	850kg