



Low-rise scissor lift RAV1450N

GTIN: 5063084192509

SKU: RAV.1450N.192509

3.2 t, electrohydraulic, with pedal operation of the safety locks, above ground

DESCRIPTION

The ideal lift for servicing tyres, brakes, suspension and bodywork. This lift of the latest generation has the following features: electro-hydraulic operation, high loading capacity and elevated lifting height, rapid cycle times. Being practical and easy to use, this lift guarantees the maximum safety to the user. A mechanical levelling system assures constant levelling of the lifting platforms regardless of weight distribution.

- Pedal release of safety locks
- Ideal for tyre service
- Extra flat 100 mm
- High lifting 1000 mm
- Quick ramp extensions from 1420 mm to 1950 mm
- Easy mobile

ACCESSORIES**Portable lift kit with 1 wheeled handle and 2 wheels**

S1450NA1

For low-rise lifts

TECHNICAL DETAILS

Scissor lift design	Low-rise scissors
Mode of drive	Electrohydraulic
Type of installation	Floor mounted
Capacity	3200kg
Max. lifting height	1000mm
Max. lifting height at floor level	955mm
Lifting time loaded	25s
Lowering time loaded	18s
Play detector	Not possible
Drive-on-height	100mm
Surface coating	Powder coated
Wheel alignment	Not possible
Length of platforms	1420mm
Width of platforms	420mm
Space of platforms	900mm
Wheel free lift	Not possible
Driving power	2,6kW
Electrical connection	230 V, 50 - 60 Hz
Phases	3
Air supply	8bar
Max. air supply	10bar
Noise level	≤70dB(A)
Length	1950mm
Width	1740mm

Height 1000

Weight 405kg

Country of Origin, customs CN