



Low-rise scissor lift RAV1450P

GTIN: 5063084193339

SKU: RAV.1450P.193339

3.2 t, electrohydraulic, with pneumatic release of the safety locks, above ground

DESCRIPTION

The ideal lift for servicing tyres, brakes, suspension and bodywork. This lift of the latest generation has the following features: electro-hydraulic operation, high loading capacity and elevated lifting height, rapid cycle times. Being practical and easy to use, this lift guarantees the maximum safety to the user. A mechanical levelling system assures constant levelling of the lifting platforms regardless of weight distribution.

- Pneumatic release of safety locks
- Ideal for tyre service
- Extra flat 100 mm
- High lifting 1000 mm
- Quick ramp extensions from 1420 mm to 1950 mm
- Easy mobile

ACCESSORIES**Portable lift kit with 1 wheeled handle and 2 wheels**

S1450NA1

For low-rise lifts

TECHNICAL DETAILS

Scissor lift design Low-rise scissors

Mode of drive Electrohydraulic

Type of installation Floor mounted

Capacity 3200kg

Max. lifting height 1000mm

Max. lifting height at floor level 955mm

Lifting time loaded 25s

Lowering time loaded 18s

Play detector Not possible

Drive-on-height 100mm

Surface coating Powder coated

Wheel alignment Not possible

Length of platforms 1420mm

Width of platforms 420mm

Height of platforms 100mm

Space of platforms 900mm

Wheel free lift Not possible

Driving power 2,6kW

Electrical connection 230/400 V, 50 Hz

Phases 3

Air supply 8bar

Max. air supply 10bar

Noise level ≤70dB(A)

Length 1950mm

Width 1740mm

Height 1000mm

Weight 405kg

Country of Origin, customs CN