



Scissor lift RAV640N.2ISI 230-400 V - 3 Ph - 60 Hz

GTIN: 5063084193001

SKU: RAV.640N2.193001

4.2 t, electrohydraulic, platform length 4600 mm, with wheel-free jack and platforms for wheel alignment, inground | 3 x 230/400 V / 60 Hz

DESCRIPTION

RAV600N Series - One Lift for Double Solutions: The new lift geometry simplifies the flush mounting pit construction. Lifts with big platforms, structured and designed for maximum stability also when loaded with large vehicles.

- Very versatile: the same lift can be flush or floor mounted
- Easy installation: easy setting up of pit
- Wide ranging applications: suitable for different operations on various types of vehicle

- Large wheel stop for high working safety.
- Integrated wheel free lift with levelling system to ensure a completely flat working surface.
- Pre-drilled platform for Ravaglioli 3D wheel alignment measuring heads brackets housing.
- The hydraulic synchronisation of the platform movements is independent of the load distribution, and is guaranteed by a patented hydraulic synchronization device.
- All pivoting points are equipped with maintenance free self-lubricating bushings.
- Base plates with levelling system for an easy installation.
- Mechanical locking device with automatic engagement and pneumatic release, ensuring maximum safety when lift is in parking position.
- The new lift geometry simplifies the flush mounting pit construction.
- Greater lifting height.

- All lifts are supplied for recessed installation - The drive on ramp kit (see accessories) enables to convert the lift from flush mounted to floor version.
- Open flush mounting for turntables: Edge-free platforms that allow the turntables to be positioned over the entire surface of the platform width - Ideal when working on vehicles with narrow track.

- Optimal sliding of jacking beam: Preinstalled galvanised guide on the inner side of the platform, which allows fast and smooth sliding of the jacking beam.

ACCESSORIES

Drive-on ramp kit

S600NA12

1350 mm, ground ramps | floor installation kit for 600N series lifts with wheel-free jack | 1 set / 2 pieces


Drive-on ramp kit

S600NA13

1800 mm, ground ramps | floor installation kit for 600N series lifts with wheel-free jack | 1 set / 2 pieces


Drive-on ramp kit

S600NA18

1560 mm, suspended ramps | floor installation kit for 600N series lifts with wheel-free jack | 1 set / 2 pieces


Drive-on ramp kit 2000 mm

S600NA20

floor installation kit for 600N series lifts with wheel-free jack | 1 set / 2 pieces


Pipe cover 1 m

S510A1

For surface installation of lifts


Rubber pads

S505A7

20 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N2.193858, RAV.650N2.193520, RAV.650N2.193667, RAV.650N6.193964, RAV.650N5.193902, RAV.660N2.193360, RAV.650N5.193018, RAV.650N6.193025, RAV.640N5.193049, RAV.640N4.192998, RAV.640N3.192981, RAV.650N2.193384 and RAV.650N5.193919 | 1 set / 4 pieces


Rubber pads

S505A6

40 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N2.193858, RAV.650N2.193520, RAV.650N2.193667, RAV.650N6.193964, RAV.650N5.193902, RAV.660N2.193360, RAV.650N5.193018, RAV.650N6.193025, RAV.640N5.193049, RAV.640N4.192998, RAV.640N3.192981, RAV.650N2.193384 and RAV.650N5.193919 | 1 set / 4 pieces


Rubber pads


S505A9

60 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N6.193964, RAV.660N2.193360, RAV.650N6.193025, RAV.640N5.193049 and RAV.640N4.192998 | 1 set / 4 pieces


Rubber pads

S505A5

120 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N2.193858, RAV.650N2.193520, RAV.650N2.193667, RAV.650N6.193964, RAV.650N5.193902, RAV.660N2.193360, RAV.650N5.193018, RAV.650N6.193025, RAV.640N5.193049, RAV.640N4.192998, RAV.640N3.192981, RAV.650N2.193384 and RAV.650N5.193919 | 1 set / 4 pieces


Rubber pads

S505A1

200 mm | suitable for RAV.640N1.193391, RAV.650N1.193742, RAV.650N2.193858, RAV.650N2.193520, RAV.650N2.193667, RAV.650N6.193964, RAV.650N5.193902, RAV.660N2.193360, RAV.650N5.193018, RAV.650N6.193025, RAV.640N5.193049, RAV.640N4.192998, RAV.640N3.192981, RAV.650N2.193384 and RAV.650N5.193919 | 1 set / 4 pieces

ACCESSORIES

Traverses for XS30-CAT

S505A2

For vans and off-road vehicles | 1 set / 2 pieces


Drive-through ramp kit

S650A5

1350 mm, ground ramps | for 600N series lifts with wheel-free jack | 1 set / 2 pieces


Drive-through ramp kit 1800 mm

S600NA17

for 600N series lifts with wheel-free jack | 1 set / 2 pieces


Drive-through ramp kit


S600NA8

1560 mm, suspended ramps | for 600N series lifts with wheel-free jack | 1 set / 2 pieces


Drive-through ramp kit

S600NA4

2000 mm, suspended ramps | for 600N series lifts with wheel-free jack | 1 set / 2 pieces


Turntable covers for 615 mm platforms

S640NA5

Spacers to completely close turntable recess | suitable for RAV.640N2.193117, RAV.640N2.193469, RAV.640N2.193001, RAV.640N2.193582, RAV.640N2.193216, RAV.640N3.192981 and RAV.640N2.193476 | 1 set / 2 pieces


Additional platform for three wheelers

S640A2

For all electro-hydraulic scissor lifts


Control unit cover for all electro-hydraulic scissor lifts

S611A4

To protect the control panel | for all models

TECHNICAL DETAILS

Scissor lift design	Scissors with runways
Mode of drive	Electrohydraulic
Type of installation	Surface mounted
Capacity	4200kg
Max. lifing height at floor level	1805mm
Lifting time	40s
Lowering time loaded	40s
Play detector	Not possible
Surface coating	Powder coated
Wheel alignment	Optional
Length of platforms	4600mm
Width of platforms	615mm
Space of platforms	870mm
Wheel free lift	Standard
Rated load capacity of wheel free lift	3500kg
Lifting travel of wheel free lift	500mm
Min. intake length wheel free lift	1390mm
Max. intake length wheel free lift	2000mm
Driving power	3,5kW
Electrical connection	230/400 V, 60 Hz
Phases	3
Air supply	280bar

Length	4600mm
Width	2100mm
Installation depth	295mm
Country of Origin, customs	IT