



Tyre changer GRS926.MOVI

GTIN: 5063084206312

SKU: RAV.GR926.206312

Mobile tyre changer for installation in vans, max. speed 8 rpm, cable hydraulic console unit, truck, rim diameter 11 – 27", max. rim width 950 mm

DESCRIPTION

Retractable truck tyre changer suitable for closed vans. Ideal for road-side tyre service, it is suitable for both truck and also for agricultural tyres.

- Electro-hydraulic movements
- Hydraulic chucking table
- After 5 sec. of no use, the motor turns off

ACCESSORIES**Bead-locking clamp for alloy rims**

G90A6

Protection for alloy rims

**Mounting lever**

G108A3

Short, patented

**Rings lever for trucks**

G108A13

**Brush wood, angled**

G108A16

For wheel assembly machines

**Grease paste for tyre mount/
dismount | 3.5 kg**

G800A37

**Clamp protections for alloy rims | 1
set / 4 pieces**

G108A2

**Bead breaker disc for snap rings**

G108A22

**Pneumatic bead pushing device for
agricultural tyres**

G108A34

TECHNICAL DETAILS

Mounting head design	Automatic
Mounting arm design	Moveable
Mounting column design	Rigid
TeqLink	Not possible
Workshop-Net	Not possible
Clamping device design	central
Min. clamping capacity	11"
Max. clamping capacity	27"
Max. rim width	37"
Min. rim diameter	11"
Max. rim diameter	27"
Tire type truck	Standard
Max. wheel width	950mm
Max. wheel diameter	1300mm
Max. wheel weight	1200kg
Automatic bead-breaking movement	Yes
Bead breaker force	16kN
Number of mounting speeds	1
Rotation speed	8rpm
Max. torque	2200Nm
Chuck motor rating	1,5kW
Driving power	2,2kW
Electrical connection	400 V, 50 Hz
Phases	3

Fuse protection	16A slow-blow
Max. air supply	130
Width	890mm
Depth	2235mm
Height	1715mm
Country of Origin, customs	IT