



Mobile column lift RAV262AGR

GTIN: 4057612815818

SKU: RAV262AGR

2 x 8.5 t, electromechanical, cable-bound, with agricultural adapters

DESCRIPTION

Pair of mobile columns to lift different tractors - The columns are equipped with front and rear adapters (S300A2). Perfect access to the vehicle: Allows tire and brake service.

- Double load protection ensures safety
- Intuitive operation
- Quick change of position by forklift possible

- Rear support adapter with additional locking bars
- Front support adapter with various support adapters
- Movable drawbar with self-deflecting steering chassis, double roller and integrated parking brake prevents unintentional rolling away of the lifting unit
- Forklift adapters allow quick and easy transport of the wheel grippers in the workshop
- Suitable for tractors with a wheelbase of at least 1100 mm
- The well-arranged control elements characterize the operator friendliness of the wheel gripper system

- The integrated charger allows charging while using the HYDROLIFT - One hour of fast charging allows another complete lifting/lowering operation.
- Double load protection due to continuously adjustable hydraulic safety device (shut-off valve) and self-locking mechanical safety catch.
- Symbols that are easy to understand and well-arranged push-buttons facilitate operation.
- Software updates are made via SD card.
- The large-volume production in our ISO-certified production facilities allows a consistently high manufacturing quality.
- Hydro Protect: For protection against external influences, the lifting cylinder is located in the lifting carriage - The motor and the hydraulic unit are also completely covered.

- Emergency stop buttons present on each column.
- Easy Drive: Low-friction rollers, literally speaking, make setting up the workplace a piece of cake.
- The synchronization control ensures absolute synchronization of all lifting units - even with unequal load distribution.

ACCESSORIES**Support trestle**

S260A1

7500 kg, 1330 - 2030 mm, height adjustable in 7 x 100 mm steps, 2 castors, U-bracket | Grey (RAL 7040)

**Support trestle**

S270A1

10000 kg, 1235 - 2040 mm, height adjustable in 6 x 100 mm steps, additionally with infinitely adjustable upper part (115 mm), 2 rollers, U-shaped holder and prismatic holder (interchangeable) | Grey (RAL 7040)

**Support trestle**

S270A2

10000 kg, 1235 - 2040 mm, height adjustable in 6 x 100 mm steps, additionally with infinitely adjustable upper part (115 mm), 3 springy wheels, U-shaped holder and prismatic holder (interchangeable), ready assembled | Grey (RAL 7040)

TECHNICAL DETAILS

Mode of drive	Electromechanical
Communication of columns	Wired
Number of lifting units	2
Capacity	17000kg
Lifting capacity per lifting unit	8500kg
Stroke	1800mm
Lifting time	135s
Lowering time	70s
Driving power per cylinder unit	3,7kW
Surface coating	Powder coated
Electrical connection	400 V, 50 Hz
Fuse protection	9,5A slow-blow
Width	1120mm
Height	2729mm
Country of Origin, customs	IT